

OZEL03XBE3MAL



- Saves energy 70% when compared to ar

- Sparkling warm white light directed radially
- Environmentally Sustainable: No mercury or hazardous materials, No UV or IR. No much heat generated
- High quality design, Robust housing
- Easy installation, can directly replace the traditional lamps
- Perfect for chandeliers, wall sconces, hospitality, hotels, restaurants, homes, shopping mall








Electrical and Technical Data

OZEL03YBE3MAL


Product Number	Watts	Voltage	Power Factor	Base	Pkg. Qty.	Color Temp (K)	CRI	Dimension DxH (mm)	Rated Avg. Life (Hrs)¹	Approx. Initial Lumens²
OZEL03XBE3MAL	_	220 - 230V	≥0.6	E14	50	2700K	80	Ø106 x 37	40,000	138
OZEL03YBE3MAL		220 - 230V	≥0.6	E14	50	2700K	80	Ø113 x 37	40,000	138

¹⁾ Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Lamp life is appreciably longer if lamps are started less frequently.


Polar Intensity Diagram



Lifetime



Dimensions (mm)





34-2, Jalan 3/146, Bandar Tasik Selatan, 57000 Kuala Lumpur, Malaysia. Tel: +603 9057 8949 Fax: +603 9057 8946 Email: sales@dpisb.com Web: www.ozlux.com